

## PISTOLA PNEUMATICA AD ARIA COMPRESSA

### Caratteristiche

- \* Valvola di attivazione rapida del fuoco
- \* Composti il controllo della profondità regolabile
- \* Potente, veloce e leggero
- \* Filtro senza fine di manutenzione
- \* Piedino per contatto rimovibile
- \* Driver a tutto tondo
- \* Il magnete del naso tiene l'ultimo chiodo nella bobina
- \* Naso resistente al catrame



### Specifiche

MODELLO	CN445R2
FIRING METHOD	Rapid fire
PESO	5.2 lbs
DIMENSIONE	10-1/2"(H) x 4-1/2"(W) x 12-3/16"(L)
CAPACITA DI CARICO	120 chiodi
PRESSIONE DI ESERCIZIO	70 - 100 psi (Regulator)
CONSUMO D'ARIA	0.047ft <sup>3</sup> /cycle at 100psi operating pressure

### Tipologia di chiodo

Guida per chiodi da 3/4" x .120" fino a 1-3/4" x .120" (19mm x 3.1mm - 45mm x 3.1mm)

### Applications

- \* Tegole bituminose
- \* Siding
- \* Assemblaggio di scatole

## PNEUMATIC GUN

### Features

- \*Rapid fire trigger valve
- \*Dial adjustable depth control
- \*Powerful, fast and light weight
- \*Maintenance free end cap filter
- \*Removable contact foot
- \*Full round driver
- \*Nose magnet holds the last nail in the coil
- \*Tar resistant nose



### Specifications

MODEL	CN445R2
FIRING METHOD	Rapid fire
WEIGHT	5.2 lbs
DIMENSIONS	10-1/2"(H) x 4-1/2"(W) x 12-3/16"(L)
LOAD CAPACITY	120 nails
OPERATING PRESSURE	70 - 100 psi (Regulator)
AIR CONSUMPTION	0.047ft3 /cycle at 100psi operating pressure

### Expendable supplies

Drives from 3/4" x .120" up to 1-3/4" x .120" (19mm x 3.1mm - 45mm x 3.1mm) roofing coil nails

### Applications

- \*Asphalt shingles
- \*Siding
- \*Box assembly
- \*Cement board