

# Prestige Ultimetal



Notified Body 0497  
n°3385/09

## General description: asphalt shingle with surface in Colored Aluminium

bituminous compound	-		<b>Blown bitumen</b>	
length	EN 544	mm	<b>1000</b>	<b>+/-5</b>
width	EN 544	mm	<b>340</b>	<b>+/-5</b>
thickness	EN 544	mm	<b>4,7</b>	<b>+/-10%</b>
exposed area	-	mm	<b>290</b>	-
Aluminium thickness	-	µm	<b>300</b>	<b>+/-10%</b>

### Physical-chemical properties

weight	-	kg/m <sup>2</sup>	<b>8,5</b>	<b>+/-10%</b>
mass of the fibreglass mat	-	g/m <sup>2</sup>	<b>2*80</b>	<b>+/-10%</b>
bitumen single layer	EN 544	g/m <sup>2</sup>	<b>&gt;3000</b>	-
mechanical resistance MD/CMD	EN 544	N/ 5 cm	<b>&gt;1500/1500</b>	-
nail resistance	EN 544	N	<b>&gt;200</b>	-
peeling	EN 544	N/cm	<b>&gt;5</b>	-

### Fire behaviour

classification according	EN 13501-5	<b>B roof (t1)</b>
classification according	EN 13501-1	<b>E</b>

### Wrapping

type	<b>cardboard</b>
m <sup>2</sup> /bundle	<b>4,06</b>
m <sup>2</sup> /pallet	<b>194,88</b>
bundles/pallet	<b>48</b>

Further info about company, product and roofing instruction on web site [www.tegolacanedese.com](http://www.tegolacanedese.com)

Tegola Canadese S.p.A.  
Via dell'Industria, 21- 31029 Vittorio V.to (TV) - I -  
Tel. +39.0438.9111 - Fax +39.0438.911260  
e-mail: [info@tegolacanedese.com](mailto:info@tegolacanedese.com)



Company certified according quality system ISO 9001 and environmental system ISO14001