

Safety BASE 2 Overlap



1381-CPR-421
Notified Body 1381
EN13707

Description: Bituminous membrane for pitched roof waterproofing.

Composition: Carrier in fiberglass, waterproofing APP modified bitumen mass; antiadherent upper and lower layer made of sand. Thermoplastic film for side overlapping.

Application: By nailing.
Application on pitched roof where slope >20°.

DIMENSIONS

				tol.
Lenght	EN 1848-1	m	15	+ 1%
Width	EN 1848-1	m	1	+ 1%

CHEMICAL AND PHYSICAL PROPERTIES

				tol.
Weight	EN 1849-1	kg/m ²	2,2	± 10%
Weight of carrier	-	g/m ²	60	± 10%
Tensile Resistance MD/CMD	EN 12311-1	N/5cm	450/300	± 15%
Elongation MD/CMD	EN 12311-1	%	>2/>2	-
Nail Shank Tear Resistance	EN 12310-1	N	>80	-
Flexibility at Low Temperatures	EN 1109	°C	<-10	-
Flow Resistance at High Temperatures	EN 1110	°C	>100	-
Waterproofing, 60 kPa/24h	EN 1928-B	-	Passed	-

PACKAGING

Type	Plastic Strip
Rolls/Pallet	30
m ² /pallet	450
kg/pallet *	1015

* Total weight includes pallet bare weight (25kg).

Safety: Material is asbestos, tar compounds and dangerous substances free.

Storage: Material is packed vertically on pallet. Keep vertically and in warehouse. Keep away from heat sources.

Other: The producer can update the tds without notice.

TEGOLA

Tegola Canadese S.p.A.
Via dell'Industria, 21 - 31029 Vittorio Veneto - Italy
T. +39 0438 9111
www.tegolaacadese.com - info@tegolaacadese.com



Rev.17 - 01/04/17 1152208801000